



ENERGREEN®

Professional Machines



POTENTE MOTORE DA
POWERFUL ENGINE WITH
50HP

RoboFIFTI 50HP



55

PENDENZA
SLOPE



* Super cingoli in gomma / Super rubber tracks
** Cingoli standard o con stiffe / Standard or studded tracks



**DESIGN A PROTEZIONE TOTALE
DESIGN FOR TOTAL PROTECTION**



**PROTEZIONI LATERALI CONTRO L'INTRUSIONE DI VEGETAZIONE
SIDE BODY PANELS AGAINST INTRUSION OF BUSHES AND VEGETATION**



**SOLLEVATORE CON ATTACCO RAPIDO
FRONT LIFTER WITH QUICK ATTACHMENT MOUNTING SYSTEM**



**ROLL-BAR INTEGRATI
INTEGRATED ROLL BAR**



**CINGOLI IN GOMMA
RUBBER TRACKS**



**SUPER CINGOLI IN GOMMA
SUPER RUBBER TRACKS**



**CINGOLI CON STAFFE
STUDDED TRACKS**



**ATTACCHI RAPIDI CON PIASTRA MULTICONNESSIONE (CEJN)
HYDRAULIC COUPLINGS WITH MULTI CONNECTION PLATE (CEJN)
OPTIONAL**



55

PENDENZA SLOPE

ROBOFIFTI

| | |
|--|---------------------------|
| Pendenza massima / Maximum gradient | 55° |
| Trasmissione / Transmission | Idrostatica / Hydrostatic |
| Velocità I° marcia / Low range speed | 0 - 4 km/h / 0 - 2.50 mph |
| Velocità II° marcia / High range speed | 0 - 7 km/h / 0 - 4.35 mph |
| Peso macchina / Machine Weight | 1220 kg / 2645 lb |

MOTORE / ENGINE

| | |
|--|--|
| Marca / Brand | Perkins |
| Modello / Type | 3 Cilindri Diesel / 3 Cylinders Diesel |
| Potenza / Power | 50 hp (36 kW) Stage V - Tier5 |
| Capacità carburante / Fuel tank | 28,5 litri / 7,5 gal. |
| Giri al minuto al lavoro / Working RPM | 2800 rpm |

RADIOCOMANDO / REMOTE CONTROL

| | |
|-----------------------------------|------------------------------|
| Marca / Brand | Autec |
| Frequenza radio / Radio frequency | 870 Mhz (EU) - 915 Mhz (US) |
| Raggio d'azione / Working range | 150 metri/meters / 492 ft |
| Joystick | Proporzionale / Proportional |
| Batteria / Battery | Ricaricabile / Rechargeable |

TESTATA TRINCIANTE / MULCHER HEAD

| | |
|-------------------------------------|-------------------------|
| Larghezza di taglio / Cutting width | 1300 mm / 51.2 in |
| Tipo di pompa / Pump type | Pistoni / Pistons |
| Portata olio / Oil Flow | 60 l/min / 15.8 gal/min |
| Pressione / Pressure | 300 bar / 4351 psi |
| Peso / Weight | 200 kg / 441 lb |

TESTATA TRINCIANTE / MULCHER HEAD

| | |
|-------------------------------------|-------------------------|
| Larghezza di taglio / Cutting width | 1535 mm / 60.7 in |
| Tipo di pompa / Pump type | Pistoni / Pistons |
| Portata olio / Oil Flow | 60 l/min / 15.8 gal/min |
| Pressione / Pressure | 300 bar / 4351 psi |
| Peso / Weight | 310 kg / 683 lb |

HEAD 130



HEAD 155



ENERGREEN®
Professional Machines

ENERGREEN S.P.A. · Via Sabbioni, 16
36026 Poiana Maggiore (Vicenza) · Italy
Tel. +39 0444 1511200 · Fax +39 0444 1511252
commerciale@energreen.it · www.energreen.it

WWW.ENERGREEN.IT

